

TR144™

Highway radial truck tire optimized for free rolling axles.



- Optimized five rib design to help resist irregular wear on free rolling axles.
- Shoulder groove designed to improve resistance to irregular wear.
- Stylish sidewall design.
- See-through grooves designed to improve wet traction.
- All steel construction for excellent retreadability.

Specifications for Tread

TR144™

Size	Load Range	Catalog Number	Tread Depth	Max Speed mph	Loaded Radius		Overall Diameter		Overall Width		Approved Rims	Min. Dual Spacing		Revs per Mile	Max. Tire Load Single				Max. Tire Load Dual			
					in.	mm.	in.	mm.	in.	mm.		in.	m		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
11R22.5	G	02041	12	75	19.0	484	40.8	1036	11.2	285	8.25, 7.50	12.5	318	508	6175	105	2800	720	5840	105	2650	720
275/80R22.5	G	39833	12	75	18.4	468	39.7	1008	11.1	281	8.25, 7.50	12.2	311	523	6175	110	2800	760	5675	110	2575	760
11R24.5	G	06457	12	75	20.0	508	43.0	1092	11.1	283	8.25, 7.50	12.5	318	482	6610	105	3000	720	6005	105	2725	720
275/80R24.5	G	27373	12	75	19.1	485	40.8	1036	10.8	274	8.25, 7.50	12.2	311	507	6175	110	2800	760	5675	110	2575	760

Note: Rim listed first is the measuring rim.

Exceeding the lawful speed limit is neither recommended nor endorsed.

Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.

BFGoodrich® tires and tubes are subject to a continuous development program. BFGoodrich Commercial Truck Tires reserves the right to change product specifications at any time without notice or obligations. Please consult rim manufacturer's load and inflation limits. Never exceed rim manufacturer's limits without permission of component manufacturer.

WARNING! SERIOUS INJURY MAY RESULT FROM:

*TIRE FAILURE DUE TO UNDERINFLATION/OVERLOADING OR MISAPPLICATION -- FOLLOW TIRE PLACARD INSTRUCTIONS IN VEHICLE. CHECK INFLATION PRESSURE FREQUENTLY WITH AN ACCURATE GAUGE
 *EXPLOSION OF TIRE/RIM ASSEMBLY DUE TO IMPROPER MOUNTING -- ONLY SPECIALLY TRAINED PERSONS SHOULD MOUNT TIRES. WHEN MOUNTING, USE SAFETY CAGE AND CLIP-ON EXTENSION AIR HOSE TO INFLATE.

CONSULT OWNER'S MANUAL FOR ADDITIONAL SAFETY INFORMATION

Load and Inflation Tables for

TR144™

S = Single configuration, or 2 tires per axle.

D = Dual configuration, or 4 tires per axle.

11R22.5 LRG

PSI		70	75	80	85	90	95	100	105	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690	720	S	6175	LBS at	105	PSI
LBS	SINGLE	9060	9540	9980	10440	11020	11460	11900	12350	D	5840	LBS at	105	PSI
	DUAL	17520	18320	19040	19800	20820	21660	22500	23360	S	2800	KG at	720	kPa
kPa	SINGLE	4100	4320	4520	4740	5000	5200	5400	5600	D	2650	KG at	720	kPa
	DUAL	7960	8320	8640	9000	9440	9840	10240	10600					

275/80R22.5 LRG

PSI	70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL		
kPa	480	520	550	590	620	660	690	720	760			
LBS	SINGLE	9000	9450	9880	10310	10740	11020	11560	11960	12350	S	6175 LBS at 110 PSI
	DUAL	16380	17200	18160	18760	19540	20280	21040	21760	22700	D	5675 LBS at 110 PSI
kPa	SINGLE	4080	4280	4480	4680	4880	5000	5240	5420	5600	S	2800 KG at 760 kPa
	DUAL	7440	7800	8240	8520	8880	9200	9560	9880	10300	D	2575 KG at 760 kPa

11R24.5 LRG

PSI	70	75	80	85	90	95	100	105	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa	480	520	550	590	620	660	690	720				
LBS	SINGLE	9640	10140	10620	11100	11680	12190	12700	13220		S	6610 LBS at 105 PSI
	DUAL	18640	19480	20280	21040	22040	22700	23360	24020		D	6005 LBS at 105 PSI
kPa	SINGLE	4380	4600	4820	5040	5300	5540	5780	6000		S	3000 KG at 720 kPa
	DUAL	8440	8840	9200	9560	10000	10320	10640	10900		D	2725 KG at 720 kPa

275/80R24.5 LRG

PSI	70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL		
kPa	480	520	550	590	620	660	690	720	760			
LBS	SINGLE	9090	9540	9880	10420	10840	11350	11670	12080	12350	S	6175 LBS at 110 PSI
	DUAL	16540	17360	18160	18960	19720	20820	21240	21980	22700	D	5675 LBS at 110 PSI
kPa	SINGLE	4120	4320	4480	4720	4920	5150	5300	5480	5600	S	2800 KG at 760 kPa
	DUAL	7480	7880	8240	8600	8960	9440	9640	9960	10300	D	2575 KG at 760 kPa

Industry load and inflation standards are in a constant state of change, and BFGoodrich continually updates its product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

DR675™

Drive radial optimized to help provide excellent traction in on/off road applications.



- Exceptional sidewall protection helps resistance to impacts.
- Deep 30/32 tread for long tread life.
- Aggressive shoulder design with off set blocks for exceptional traction.
- Robust 4-belt construction for outstanding protection against road hazards and dependable retreadability.
- Tread compound tailored for rigor of on/off road applications.

Specifications for Tread

DR675™

Size	Load Range	Catalog Number	Tread Depth	Max Speed mph	Loaded Radius		Overall Diameter		Overall Width		Approved Rims	Min. Dual Spacing		Revs per Mile	Max. Tire Load Single				Max. Tire Load Dual			
					in.	mm.	in.	mm.	in.	mm.		in.	m		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
11R22.5	H	47237	30	65	19.6	498	41.9	1064	11.2	284	8.25, 7.50	12.5	318	494	6610	120	3000	830	6005	120	2725	830
11R24.5	H	80401	30	65	20.5	521	44.0	1118	11.3	287	8.25, 7.50	12.5	318	471	7160	120	3250	830	6610	120	3000	830

Note: Rim listed first is the measuring rim.

Exceeding the lawful speed limit is neither recommended nor endorsed.

Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.

BFGoodrich® tires and tubes are subject to a continuous development program. BFGoodrich Commercial Truck Tires reserves the right to change product specifications at any time without notice or obligations.

Please consult rim manufacturer's load and inflation limits. Never exceed rim manufacturer's limits without permission of component manufacturer.

WARNING! SERIOUS INJURY MAY RESULT FROM:

*TIRE FAILURE DUE TO UNDERINFLATION/OVERLOADING OR MISAPPLICATION -- FOLLOW TIRE PLACARD INSTRUCTIONS IN VEHICLE. CHECK INFLATION PRESSURE FREQUENTLY WITH AN ACCURATE GAUGE

*EXPLOSION OF TIRE/RIM ASSEMBLY DUE TO IMPROPER MOUNTING -- ONLY SPECIALLY TRAINED PERSONS SHOULD MOUNT TIRES. WHEN MOUNTING, USE SAFETY CAGE AND CLIP-ON EXTENSION AIR HOSE TO INFLATE.

CONSULT OWNER'S MANUAL FOR ADDITIONAL SAFETY INFORMATION

Load and Inflation Tables for

DR675™

S = Single configuration, or 2 tires per axle.

D = Dual configuration, or 4 tires per axle.

11R22.5 LRH

PSI		75	80	85	90	95	100	105	110	115	120		MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		520	550	590	620	660	690	720	760	790	830		S	6610	LBS at	120	PSI
LBS	SINGLE	9540	9980	10440	11020	11460	11900	12350	12640	12930	13220		D	6005	LBS at	120	PSI
	DUAL	18320	19040	19800	20820	21660	22500	23360	23580	23800	24020		S	3000	KG at	830	kPa
kPa	SINGLE	4320	4520	4740	5000	5200	5400	5600	5740	5880	6000		D	2725	KG at	830	kPa
	DUAL	8320	8640	9000	9440	9840	10240	10600	10720	10840	10900						

11R24.5 LRH

PSI		75	80	85	90	95	100	105	110	115	120		MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		520	550	590	620	660	690	720	760	790	830		S	7160	LBS at	120	PSI
LBS	SINGLE	10140	10620	11100	11680	12190	12700	13220	13580	13940	14320		D	6610	LBS at	120	PSI
	DUAL	19480	20280	21040	22040	22700	23360	24020	24820	25620	26440		S	3250	KG at	830	kPa
kPa	SINGLE	4600	4820	5040	5300	5540	5780	6000	6160	6320	6500		D	3000	KG at	830	kPa
	DUAL	8840	9200	9560	10000	10320	10640	10900	11280	11640	12000						

Industry load and inflation standards are in a constant state of change, and BFGoodrich continually updates its product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

DR444™

Highway drive radial optimized for long mileage and even wear.



- Deep 28/32nds tread to promote long tread life.
- Aggressive tread design to help deliver high traction.
- V-shape groove design to help improve self-cleaning of the tread surface.
- All-steel construction for excellent retreadability.

Specifications for Tread DR444™

Size	Load Range	Catalog Number	Tread Depth	Max Speed mph	Loaded Radius		Overall Diameter		Overall Width		Approved Rims	Min. Dual Spacing		Revs per Mile	Max. Tire Load Single				Max. Tire Load Dual			
					in.	mm.	in.	mm.	in.	mm.		in.	m		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
11R22.5	H	98035	28	75	19.4	493	41.8	1062	11.2	284	8.25, 7.50	12.5	318	497	6610	120	3000	830	6005	120	2725	830
11R22.5	G	77081	28	75	19.4	493	41.8	1062	11.2	284	8.25, 7.50	12.5	318	497	6175	105	2800	720	5840	105	2650	720
275/80R22.5	G	90375	28	75	18.9	480	40.6	1032	10.9	277	8.25, 7.50	12.2	311	511	6175	110	2800	760	5675	110	2575	760
11R24.5	G	52321	28	75	20.5	521	43.9	1116	11.0	279	8.25, 7.50	12.5	318	472	6610	105	3000	720	6005	105	2725	720
11R24.5	H	89861	28	75	20.5	521	43.9	1116	11.0	279	8.25, 7.50	12.5	318	472	7160	120	3250	830	6610	120	3000	830
275/80R24.5	G	55617	28	75	19.5	495	41.9	1064	10.6	269	8.25, 7.50	12.2	311	500	6175	110	2800	760	5675	110	2575	760

Note: Rim listed first is the measuring rim.
 Exceeding the lawful speed limit is neither recommended nor endorsed.
 Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
 BFGoodrich® tires and tubes are subject to a continuous development program. BFGoodrich Commercial Truck Tires reserves the right to change product specifications at any time without notice or obligations.
 Please consult rim manufacturer's load and inflation limits. Never exceed rim manufacturer's limits without permission of component manufacturer.

WARNING! SERIOUS INJURY MAY RESULT FROM:
 *TIRE FAILURE DUE TO UNDERINFLATION/OVERLOADING OR MISAPPLICATION -- FOLLOW TIRE PLACARD INSTRUCTIONS IN VEHICLE. CHECK INFLATION PRESSURE FREQUENTLY WITH AN ACCURATE GAUGE
 *EXPLOSION OF TIRE/RIM ASSEMBLY DUE TO IMPROPER MOUNTING -- ONLY SPECIALLY TRAINED PERSONS SHOULD MOUNT TIRES. WHEN MOUNTING, USE SAFETY CAGE AND CLIP-ON EXTENSION AIR HOSE TO INFLATE.
 CONSULT OWNER'S MANUAL FOR ADDITIONAL SAFETY INFORMATION

Load and Inflation Tables for DR444™

S = Single configuration, or 2 tires per axle.
 D = Dual configuration, or 4 tires per axle.

11R22.5 LRG

PSI	70	75	80	85	90	95	100	105	MAXIMUM LOAD AND PRESSURE ON SIDEWALL
kPa	480	520	550	590	620	660	690	720	
LBS	SINGLE	9060	9540	9980	10440	11020	11460	11900	S 6175 LBS at 105 PSI
	DUAL	17520	18320	19040	19800	20820	21660	22500	D 5840 LBS at 105 PSI
kPa	SINGLE	4100	4320	4520	4740	5000	5200	5400	S 2800 KG at 720 kPa
	DUAL	7960	8320	8640	9000	9440	9840	10240	D 2650 KG at 720 kPa

11R22.5 LRH

PSI		75	80	85	90	95	100	105	110	115	120		MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	9540	9980	10440	11020	11460	11900	12350	12640	12930	13220		S	6610	LBS at	120 PSI
	DUAL	18320	19040	19800	20820	21660	22500	23360	23580	23800	24020		D	6005	LBS at	120 PSI
kPa	SINGLE	4320	4520	4740	5000	5200	5400	5600	5740	5880	6000		S	3000	KG at	830 kPa
	DUAL	8320	8640	9000	9440	9840	10240	10600	10720	10840	10900		D	2725	KG at	830 kPa

275/80R22.5 LRG

PSI		70	75	80	85	90	95	100	105	110		MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		480	520	550	590	620	660	690	720	760					
LBS	SINGLE	9000	9450	9880	10310	10740	11020	11560	11960	12350		S	6175	LBS at	110 PSI
	DUAL	16380	17200	18160	18760	19540	20280	21040	21760	22700		D	5675	LBS at	110 PSI
kPa	SINGLE	4080	4280	4480	4680	4880	5000	5240	5420	5600		S	2800	KG at	760 kPa
	DUAL	7440	7800	8240	8520	8880	9200	9560	9880	10300		D	2575	KG at	760 kPa

11R24.5 LRG

PSI		70	75	80	85	90	95	100	105		MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		480	520	550	590	620	660	690	720					
LBS	SINGLE	9640	10140	10620	11100	11680	12190	12700	13220		S	6610	LBS at	105 PSI
	DUAL	18640	19480	20280	21040	22040	22700	23360	24020		D	6005	LBS at	105 PSI
kPa	SINGLE	4380	4600	4820	5040	5300	5540	5780	6000		S	3000	KG at	720 kPa
	DUAL	8440	8840	9200	9560	10000	10320	10640	10900		D	2725	KG at	720 kPa

11R24.5 LRH

PSI		75	80	85	90	95	100	105	110	115	120		MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	10140	10620	11100	11680	12190	12700	13220	13580	13940	14320		S	7160	LBS at	120 PSI
	DUAL	19480	20280	21040	22040	22700	23360	24020	24820	25620	26440		D	6610	LBS at	120 PSI
kPa	SINGLE	4600	4820	5040	5300	5540	5780	6000	6160	6320	6500		S	3250	KG at	830 kPa
	DUAL	8840	9200	9560	10000	10320	10640	10900	11280	11640	12000		D	3000	KG at	830 kPa

275/80R24.5 LRG

PSI		70	75	80	85	90	95	100	105	110		MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		480	520	550	590	620	660	690	720	760					
LBS	SINGLE	9090	9540	9880	10420	10840	11350	11670	12080	12350		S	6175	LBS at	110 PSI
	DUAL	16540	17360	18160	18960	19720	20820	21240	21980	22700		D	5675	LBS at	110 PSI
kPa	SINGLE	4120	4320	4480	4720	4920	5150	5300	5480	5600		S	2800	KG at	760 kPa
	DUAL	7480	7880	8240	8600	8960	9440	9640	9960	10300		D	2575	KG at	760 kPa

Industry load and inflation standards are in a constant state of change, and BFGoodrich continually updates its product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

DR424™

Regional drive radial optimized for long mileage and excellent traction



- Open shoulder design helps provide exceptional traction on dry, wet and snow covered surfaces.
- Full depth sipes for excellent traction throughout life of tire.
- Tread compound tailored for regional service.
- All-steel construction for excellent retreadability.

Specifications for Tread

DR424™

Size	Load Range	Catalog Number	Tread Depth	Max Speed mph	Loaded Radius		Overall Diameter		Overall Width		Approved Rims	Min. Dual Spacing		Revs per Mile	Max. Tire Load Single				Max. Tire Load Dual			
					in.	mm.	in.	mm.	in.	mm.		in.	m		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
10R22.5	G	57721	21	75	18.6	474	40.0	1016	10.5	266	8.25, 8.25, 7.50	11.7	297	517	5675	115	2575	790	5355	115	2430	790
11R22.5	G	66509	24	75	19.3	489	41.5	1055	11.2	284	8.25, 7.50	12.5	318	500	6175	105	2800	720	5840	105	2650	720
275/80R22.5	G	85264	24	75	18.8	477	40.3	1024	10.9	277	8.25, 7.50	12.2	311	514	6175	110	2800	760	5675	110	2575	760

Note: Rim listed first is the measuring rim.

Exceeding the lawful speed limit is neither recommended nor endorsed.

Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.

BFGoodrich® tires and tubes are subject to a continuous development program. BFGoodrich Commercial Truck Tires reserves the right to change product specifications at any time without notice or obligations.

Please consult rim manufacturer's load and inflation limits. Never exceed rim manufacturer's limits without permission of component manufacturer.

WARNING! SERIOUS INJURY MAY RESULT FROM:

*TIRE FAILURE DUE TO UNDERINFLATION/OVERLOADING OR MISAPPLICATION -- FOLLOW TIRE PLACARD INSTRUCTIONS IN VEHICLE. CHECK INFLATION PRESSURE FREQUENTLY WITH AN ACCURATE GAUGE

*EXPLOSION OF TIRE/RIM ASSEMBLY DUE TO IMPROPER MOUNTING -- ONLY SPECIALLY TRAINED PERSONS SHOULD MOUNT TIRES. WHEN MOUNTING, USE SAFETY CAGE AND CLIP-ON EXTENSION AIR HOSE TO INFLATE.

CONSULT OWNER'S MANUAL FOR ADDITIONAL SAFETY INFORMATION

Load and Inflation Tables for

DR424™

S = Single configuration, or 2 tires per axle.

D = Dual configuration, or 4 tires per axle.

10R22.5 LRG

PSI	70	75	80	85	90	95	100	105	110	115	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa	480	520	550	590	620	660	690	720	760	790				
LBS	SINGLE	8160	8560	8960	9350	9700	10050	10410	10720	11030	11350	S	5675	LBS at 115 PSI
	DUAL	15440	16180	16920	17640	18340	19040	19760	20300	20840	21420	D	5355	LBS at 115 PSI
kPa	SINGLE	3700	3880	4060	4240	4400	4560	4720	4860	5000	5150	S	2575	KG at 790 kPa
	DUAL	7000	7320	7640	8000	8320	8640	8960	9200	9440	9720	D	2430	KG at 790 kPa

11R22.5 LRG

PSI	70	75	80	85	90	95	100	105	MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
kPa	480	520	550	590	620	660	690	720						
LBS	SINGLE	9060	9540	9980	10440	11020	11460	11900	12350			S	6175	LBS at 105 PSI
	DUAL	17520	18320	19040	19800	20820	21660	22500	23360			D	5840	LBS at 105 PSI
kPa	SINGLE	4100	4320	4520	4740	5000	5200	5400	5600			S	2800	KG at 720 kPa
	DUAL	7960	8320	8640	9000	9440	9840	10240	10600			D	2650	KG at 720 kPa

275/80R22.5 LRG

PSI		70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL								
kPa		480	520	550	590	620	660	690	720	760									
LBS	SINGLE	9000	9450	9880	10310	10740	11020	11560	11960	12350	S	6175	LBS at	110	PSI				
	DUAL	16380	17200	18160	18760	19540	20280	21040	21760	22700	D	5675	LBS at	110	PSI				
kPa	SINGLE	4080	4280	4480	4680	4880	5000	5240	5420	5600	S	2800	KG at	760	kPa				
	DUAL	7440	7800	8240	8520	8880	9200	9560	9880	10300	D	2575	KG at	760	kPa				

Industry load and inflation standards are in a constant state of change, and BFGoodrich continually updates its product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

On/Off Road

ST576™

All-wheel-position radial optimized to help withstand the rigor of on/off road applications.



- Exceptional sidewall protection helps improve resistance to impacts.
- Deep 21/32 tread depth for long original tread life.
- Aggressive shoulder design with off set blocks for exceptional traction.
- Robust 4-belt construction for excellent protection against road hazards and dependable retreadability.
- Specially formulated compound for optimized tread life and resistance to the abrasion and cutting associated with on/off road use.

Specifications for Tread

ST576™

Size	Load Range	Catalog Number	Tread Depth	Max Speed mph	Loaded Radius		Overall Diameter		Overall Width		Approved Rims	Min. Dual Spacing		Revs per Mile	Max. Tire Load Single				Max. Tire Load Dual			
					in.	mm.	in.	mm.	in.	mm.		in.	m		in.	m	lbs.	psi	kg.	kPa	lbs.	psi
11R22.5	H	50677	21	65	19.3	489	41.2	1047	11.2	284	8.25, 7.50	12.5	318	502	6610	120	3000	830	6005	120	2725	830
11R24.5	H	86409	21	65	20.2	512	43.2	1098	11.2	284	8.25, 7.50	12.5	318	479	7160	120	3250	830	6610	120	3000	830

Note: Rim listed first is the measuring rim.

Exceeding the lawful speed limit is neither recommended nor endorsed.

Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.

BFGoodrich® tires and tubes are subject to a continuous development program. BFGoodrich Commercial Truck Tires reserves the right to change product specifications at any time without notice or obligations.

Please consult rim manufacturer's load and inflation limits. Never exceed rim manufacturer's limits without permission of component manufacturer.

WARNING! SERIOUS INJURY MAY RESULT FROM:

*TIRE FAILURE DUE TO UNDERINFLATION/OVERLOADING OR MISAPPLICATION -- FOLLOW TIRE PLACARD INSTRUCTIONS IN VEHICLE. CHECK INFLATION PRESSURE FREQUENTLY WITH AN ACCURATE GAUGE
*EXPLOSION OF TIRE/RIM ASSEMBLY DUE TO IMPROPER MOUNTING -- ONLY SPECIALLY TRAINED PERSONS SHOULD MOUNT TIRES. WHEN MOUNTING, USE SAFETY CAGE AND CLIP-ON EXTENSION AIR HOSE TO INFLATE.

CONSULT OWNER'S MANUAL FOR ADDITIONAL SAFETY INFORMATION

Load and Inflation Tables for

ST576™

S = Single configuration, or 2 tires per axle.
D = Dual configuration, or 4 tires per axle.

11R22.5 LRH

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		520	550	590	620	660	690	720	760	790	830				
LBS	SINGLE	9540	9980	10440	11020	11460	11900	12350	12640	12930	13220	S	6610	LBS at	120 PSI
	DUAL	18320	19040	19800	20820	21660	22500	23360	23580	23800	24020	D	6005	LBS at	120 PSI
kPa	SINGLE	4320	4520	4740	5000	5200	5400	5600	5740	5880	6000	S	3000	KG at	830 kPa
	DUAL	8320	8640	9000	9440	9840	10240	10600	10720	10840	10900	D	2725	KG at	830 kPa

11R24.5 LRH

PSI		75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL			
kPa		520	550	590	620	660	690	720	760	790	830				
LBS	SINGLE	10140	10620	11100	11680	12190	12700	13220	13580	13940	14320	S	7160	LBS at	120 PSI
	DUAL	19480	20280	21040	22040	22700	23360	24020	24820	25620	26440	D	6610	LBS at	120 PSI
kPa	SINGLE	4600	4820	5040	5300	5540	5780	6000	6160	6320	6500	S	3250	KG at	830 kPa
	DUAL	8840	9200	9560	10000	10320	10640	10900	11280	11640	12000	D	3000	KG at	830 kPa

Industry load and inflation standards are in a constant state of change, and BFGoodrich continually updates its product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

ST565™ Wide Base

All-wheel-position wide base radial optimized to help withstand the rigor of on/off road applications.



- Offset shoulder block design helps improve traction in soft soil.
- Deep circumferential grooves channel water to help improve wet road traction.
- Size specific bridging (high bridges in 385, low bridges in 445) define smooth ride and high traction where necessary.
- Variable pitch wall angles designed to reduce the risk of stone retention and stone drilling.
- Wide-protector ply for resistance to penetrating objects.
- Chip and cut resistant compound.

Specifications for Tread

ST565™ Wide Base

Size	Load Range	Catalog Number	Tread Depth	Max Speed mph	Loaded Radius		Overall Diameter		Overall Width		Approved Rims	Min. Dual Spacing		Revs per Mile	Max. Tire Load Single				Max. Tire Load Dual			
					in.	mm.	in.	mm.	in.	mm.		in.	m		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
385/65R22.5	J	64873	19	65	19.5	496	42.2	1071	14.9	378	11.75, 12.25			493	9370	120	4250	830				
425/65R22.5	L	49039	19	65	20.4	518	44.4	1128	16.5	420	13.00, 12.25			470	11400	120	5150	830				
445/65R22.5	L	42131	20	65	20.9	530	45.5	1156	17.7	450	14.00, 13.00			458	12300	120	5600	830				

Note: Rim listed first is the measuring rim.

Exceeding the lawful speed limit is neither recommended nor endorsed.

Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.

BFGoodrich® tires and tubes are subject to a continuous development program. BFGoodrich Commercial Truck Tires reserves the right to change product specifications at any time without notice or obligations.

Please consult rim manufacturer's load and inflation limits. Never exceed rim manufacturer's limits without permission of component manufacturer.

WARNING! SERIOUS INJURY MAY RESULT FROM:

*TIRE FAILURE DUE TO UNDERINFLATION/OVERLOADING OR MISAPPLICATION -- FOLLOW TIRE PLACARD INSTRUCTIONS IN VEHICLE. CHECK INFLATION PRESSURE FREQUENTLY WITH AN ACCURATE GAUGE

*EXPLOSION OF TIRE/RIM ASSEMBLY DUE TO IMPROPER MOUNTING -- ONLY SPECIALLY TRAINED PERSONS SHOULD MOUNT TIRES. WHEN MOUNTING, USE SAFETY CAGE AND CLIP-ON EXTENSION AIR HOSE TO INFLATE.

CONSULT OWNER'S MANUAL FOR ADDITIONAL SAFETY INFORMATION

Load and Inflation Tables for

ST565™ Wide Base

S = Single configuration, or 2 tires per axle.

D = Dual configuration, or 4 tires per axle.

385/65R22.5 LRJ

PSI	75	80	85	90	95	100	105	110	115	120		MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
kPa	520	550	590	620	660	690	720	760	790	830							
LBS	SINGLE	13440	13880	14700	15300	16100	16460	17020	17640	18100	18740		S	9370	LBS at	120	PSI
	DUAL												D		LBS at		PSI
kPa	SINGLE	6120	6300	6700	6940	7300	7480	7700	8000	8200	8500		S	4250	KG at	830	kPa
	DUAL												D		KG at		kPa

425/65R22.5 LRL

PSI	75	80	85	90	95	100	105	110	115	120		MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
kPa	520	550	590	620	660	690	720	760	790	830							
LBS	SINGLE	15980	16540	17480	18200	18740	19580	20200	21000	21400	22800		S	11400	LBS at	120	PSI
	DUAL												D		LBS at		PSI
kPa	SINGLE	7280	7500	7960	8260	8500	8880	9160	9500	9760	10300		S	5150	KG at	830	kPa
	DUAL												D		KG at		kPa

445/65R22.5 LRL

PSI	75	80	85	90	95	100	105	110	115	120		MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
kPa	520	550	590	620	660	690	720	760	790	830							
LBS	SINGLE	17320	18180	18960	19740	20400	21200	22000	22800	23400	24600		S	12300	LBS at	120	PSI
	DUAL												D		LBS at		PSI
kPa	SINGLE	7900	8250	8640	8940	9250	9640	9920	10300	10580	11200		S	5600	KG at	830	kPa
	DUAL												D		KG at		kPa

Industry load and inflation standards are in a constant state of change, and BFGoodrich continually updates its product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

ST244™

All-wheel-position highway radial optimized for the steer axle.



- Wider tread for improved wear and handling.
- Unique decoupling groove helps resist irregular wear.
- Five-rib, four-groove design for excellent water evacuation.
- Over 1900 miniature sipes for excellent traction and resistance to irregular wear.
- All-steel construction for exceptional retreadability.

Specifications for Tread

ST244™

Size	Load Range	Catalog Number	Tread Depth	Max Speed mph	Loaded Radius		Overall Diameter		Overall Width		Approved Rims	Min. Dual Spacing		Revs per Mile	Max. Tire Load Single				Max. Tire Load Dual			
					in.	mm.	in.	mm.	in.	mm.		in.	m		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
11R22.5	G	40525	18	75	19.1	486	41.1	1043	10.5	267	8.25, 7.50	12.5	318	505	6175	105	2800	720	5840	105	2650	720
11R22.5	H	92401	18	75	19.2	487	41.1	1044	12.2	309	8.25, 7.50	12.5	318	505	6610	120	3000	830	6005	120	2725	830
275/80R22.5	G	61456	18	75	18.6	472	40.0	1016	10.9	277	8.25, 7.50	12.2	311	519	6175	110	2800	760	5675	110	2575	760
11R24.5	G	51477	18	75	20.2	513	43.3	1100	11.0	279	8.25, 7.50	12.5	318	478	6610	105	3000	720	6005	105	2725	720
11R24.5	H	58109	18	75	20.2	513	43.3	1100	11.0	279	8.25, 7.50	12.5	318	478	7160	120	3250	830	6610	120	3000	830
275/80R24.5	G	77897	18	75	19.2	488	41.3	1049	10.6	269	8.25, 7.50	12.2	311	502	6175	110	2800	760	5675	110	2575	760

Note: Rim listed first is the measuring rim.
 Exceeding the lawful speed limit is neither recommended nor endorsed.
 Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.
 BFGoodrich® tires and tubes are subject to a continuous development program. BFGoodrich Commercial Truck Tires reserves the right to change product specifications at any time without notice or obligations.
 Please consult rim manufacturer's load and inflation limits. Never exceed rim manufacturer's limits without permission of component manufacturer.

WARNING! SERIOUS INJURY MAY RESULT FROM:
 *TIRE FAILURE DUE TO UNDERINFLATION/OVERLOADING OR MISAPPLICATION -- FOLLOW TIRE PLACARD INSTRUCTIONS IN VEHICLE. CHECK INFLATION PRESSURE FREQUENTLY WITH AN ACCURATE GAUGE
 *EXPLOSION OF TIRE/RIM ASSEMBLY DUE TO IMPROPER MOUNTING -- ONLY SPECIALLY TRAINED PERSONS SHOULD MOUNT TIRES. WHEN MOUNTING, USE SAFETY CAGE AND CLIP-ON EXTENSION AIR HOSE
 TO INFLATE.
 CONSULT OWNER'S MANUAL FOR ADDITIONAL SAFETY INFORMATION

Load and Inflation Tables for

ST244™

S = Single configuration, or 2 tires per axle.
D = Dual configuration, or 4 tires per axle.

11R22.5 LRG

PSI		70	75	80	85	90	95	100	105	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa		480	520	550	590	620	660	690	720	S	6175	LBS at	105	PSI
LBS	SINGLE	9060	9540	9980	10440	11020	11460	11900	12350	D	5840	LBS at	105	PSI
	DUAL	17520	18320	19040	19800	20820	21660	22500	23360	S	2800	KG at	720	kPa
kPa	SINGLE	4100	4320	4520	4740	5000	5200	5400	5600	D	2650	KG at	720	kPa
	DUAL	7960	8320	8640	9000	9440	9840	10240	10600					

11R22.5 LRH

PSI		75	80	85	90	95	100	105	110	115	120		MAXIMUM LOAD AND PRESSURE ON SIDEWALL	
kPa		520	550	590	620	660	690	720	760	790	830			
LBS	SINGLE	9540	9980	10440	11020	11460	11900	12350	12640	12930	13220		S	6610 LBS at 120 PSI
	DUAL	18320	19040	19800	20820	21660	22500	23360	23580	23800	24020		D	6005 LBS at 120 PSI
kPa	SINGLE	4320	4520	4740	5000	5200	5400	5600	5740	5880	6000		S	3000 KG at 830 kPa
	DUAL	8320	8640	9000	9440	9840	10240	10600	10720	10840	10900		D	2725 KG at 830 kPa

275/80R22.5 LRG

PSI		70	75	80	85	90	95	100	105	110		MAXIMUM LOAD AND PRESSURE ON SIDEWALL	
kPa		480	520	550	590	620	660	690	720	760			
LBS	SINGLE	9000	9450	9880	10310	10740	11020	11560	11960	12350		S	6175 LBS at 110 PSI
	DUAL	16380	17200	18160	18760	19540	20280	21040	21760	22700		D	5675 LBS at 110 PSI
kPa	SINGLE	4080	4280	4480	4680	4880	5000	5240	5420	5600		S	2800 KG at 760 kPa
	DUAL	7440	7800	8240	8520	8880	9200	9560	9880	10300		D	2575 KG at 760 kPa

11R24.5 LRG

PSI		70	75	80	85	90	95	100	105		MAXIMUM LOAD AND PRESSURE ON SIDEWALL	
kPa		480	520	550	590	620	660	690	720			
LBS	SINGLE	9640	10140	10620	11100	11680	12190	12700	13220		S	6610 LBS at 105 PSI
	DUAL	18640	19480	20280	21040	22040	22700	23360	24020		D	6005 LBS at 105 PSI
kPa	SINGLE	4380	4600	4820	5040	5300	5540	5780	6000		S	3000 KG at 720 kPa
	DUAL	8440	8840	9200	9560	10000	10320	10640	10900		D	2725 KG at 720 kPa

11R24.5 LRH

PSI		75	80	85	90	95	100	105	110	115	120		MAXIMUM LOAD AND PRESSURE ON SIDEWALL	
kPa		520	550	590	620	660	690	720	760	790	830			
LBS	SINGLE	10140	10620	11100	11680	12190	12700	13220	13580	13940	14320		S	7160 LBS at 120 PSI
	DUAL	19480	20280	21040	22040	22700	23360	24020	24820	25620	26440		D	6610 LBS at 120 PSI
kPa	SINGLE	4600	4820	5040	5300	5540	5780	6000	6160	6320	6500		S	3250 KG at 830 kPa
	DUAL	8840	9200	9560	10000	10320	10640	10900	11280	11640	12000		D	3000 KG at 830 kPa

275/80R24.5 LRG

PSI		70	75	80	85	90	95	100	105	110		MAXIMUM LOAD AND PRESSURE ON SIDEWALL	
kPa		480	520	550	590	620	660	690	720	760			
LBS	SINGLE	9090	9540	9880	10420	10840	11350	11670	12080	12350		S	6175 LBS at 110 PSI
	DUAL	16540	17360	18160	18960	19720	20820	21240	21980	22700		D	5675 LBS at 110 PSI
kPa	SINGLE	4120	4320	4480	4720	4920	5150	5300	5480	5600		S	2800 KG at 760 kPa
	DUAL	7480	7880	8240	8600	8960	9440	9640	9960	10300		D	2575 KG at 760 kPa

Industry load and inflation standards are in a constant state of change, and BFGoodrich continually updates its product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.

ST230™

All-wheel-position highway radial optimized for high scrub applications.



- Solid shoulders to help resist wear in high scrub environments.
- Five rib, four groove design to offer exceptional water evacuation.
- Over 1900 miniature sipes for excellent traction and resistance to irregular wear.
- All steel construction for excellent retreadability.

Specifications for Tread

ST230™

Size	Load Range	Catalog Number	Tread Depth	Max Speed mph	Loaded Radius		Overall Diameter		Overall Width		Approved Rims	Min. Dual Spacing		Revs per Mile	Max. Tire Load Single				Max. Tire Load Dual			
					in.	mm.	in.	mm.	in.	mm.		in.	m		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
225/70R19.5	G	74208	15	75	14.8	376	32.1	815	9.2	233	6.00, 6.75	10.0	254	647	3970	110	1800	760	3750	110	1700	760
245/70R19.5	G	89688	16	75	15.6	396	33.5	852	9.7	246	6.75, 7.50	10.9	277	624	4540	110	2060	760	4300	110	1950	760
10R22.5	G	62086	17	75	18.6	472	39.8	1012	10.0	255	7.50, 8.25, 6.75	11.4	288	521	5675	115	2575	790	5355	115	2430	790
11R22.5	H	68045	18	75	19.1	486	41.1	1043	11.1	282	8.25, 7.50	12.5	318	505	6610	120	3000	830	6005	120	2725	830
12R22.5	H	63223	19	75	19.8	503	42.4	1077	11.3	286	8.25, 9.00	13.2	335	487	7390	120	3350	830	6780	120	3075	830
255/70R22.5	H	95971	17	75	17.1	435	36.6	929	10.2	258	8.25, 7.50	11.6	295	566	5510	120	2500	830	5070	120	2300	830
275/80R22.5	G	50614	18	75	18.6	472	40.0	1016	10.9	277	8.25, 7.50	12.2	311	518	6175	110	2800	760	5675	110	2575	760
275/80R22.5	G	10339	18	75	18.6	472	40.0	1016	10.9	277	8.25, 7.50	12.2	311	519	6175	110	2800	760	5675	110	2575	760
315/80R22.5	L	55458	17	75	19.6	499	42.4	1076	12.5	317	9.00	13.8	351	489	9090	130	4125	900	8270	130	3750	900
11R24.5	H	79184	18	75	20.2	513	43.3	1100	11.0	279	8.25, 7.50	12.5	318	478	7160	120	3250	830	6610	120	3000	830
275/80R24.5	G	71892	18	75	19.2	488	41.3	1049	10.6	269	8.25, 7.50	12.2	311	503	6175	110	2800	760	5675	110	2575	760

Note: Rim listed first is the measuring rim.

Exceeding the lawful speed limit is neither recommended nor endorsed.

Overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in rim width. Minimum dual spacing should be adjusted accordingly.

BFGoodrich® tires and tubes are subject to a continuous development program. BFGoodrich Commercial Truck Tires reserves the right to change product specifications at any time without notice or obligations.

Please consult rim manufacturer's load and inflation limits. Never exceed rim manufacturer's limits without permission of component manufacturer.

WARNING! SERIOUS INJURY MAY RESULT FROM:

*TIRE FAILURE DUE TO UNDERINFLATION/OVERLOADING OR MISAPPLICATION – FOLLOW TIRE PLACARD INSTRUCTIONS IN VEHICLE. CHECK INFLATION PRESSURE FREQUENTLY WITH AN ACCURATE GAUGE
 *EXPLOSION OF TIRE/RIM ASSEMBLY DUE TO IMPROPER MOUNTING – ONLY SPECIALLY TRAINED PERSONS SHOULD MOUNT TIRES. WHEN MOUNTING, USE SAFETY CAGE AND CLIP-ON EXTENSION AIR HOSE TO INFLATE.

CONSULT OWNER'S MANUAL FOR ADDITIONAL SAFETY INFORMATION

Load and Inflation Tables for

ST230™

S = Single configuration, or 2 tires per axle.

D = Dual configuration, or 4 tires per axle.

225/70R19.5 LRG

PSI	65	70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL
kPa	450	480	520	550	590	620	660	690	720	760	
LBS	SINGLE	5510	5790	6080	6390	6630	6900	7280	7430	7690	S 3970 LBS at 110 PSI
	DUAL	10400	10880	11440	12000	12460	12980	13660	13960	14460	D 3750 LBS at 110 PSI
kPa	SINGLE	2500	2620	2760	2900	3000	3140	3300	3380	3480	S 1800 KG at 760 kPa
	DUAL	4720	4920	5200	5440	5640	5880	6200	6320	6560	D 1700 KG at 760 kPa

315/80R22.5 LRL

PSI	85	90	95	100	105	110	115	120	125	130	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	590	620	660	690	720	760	790	830	860	900					
LBS	SINGLE	12830	13340	13880	14380	14880	15220	15840	16540	17620	18180	S	9090	LBS at 130	PSI
	DUAL	23360	24280	25580	26180	27080	27760	28840	30440	32040	33080	D	8270	LBS at 130	PSI
kPa	SINGLE	5820	6060	6300	6520	6740	6900	7180	7500	7960	8250	S	4125	KG at 900	kPa
	DUAL	10600	11000	11600	11880	12280	12600	13080	13800	14480	15000	D	3750	KG at 900	kPa

11R24.5 LRH

PSI	75	80	85	90	95	100	105	110	115	120	MAXIMUM LOAD AND PRESSURE ON SIDEWALL				
kPa	520	550	590	620	660	690	720	760	790	830					
LBS	SINGLE	10140	10620	11100	11680	12190	12700	13220	13580	13940	14320	S	7160	LBS at 120	PSI
	DUAL	19480	20280	21040	22040	22700	23360	24020	24820	25620	26440	D	6610	LBS at 120	PSI
kPa	SINGLE	4600	4820	5040	5300	5540	5780	6000	6160	6320	6500	S	3250	KG at 830	kPa
	DUAL	8840	9200	9560	10000	10320	10640	10900	11280	11640	12000	D	3000	KG at 830	kPa

275/80R24.5 LRG

PSI	70	75	80	85	90	95	100	105	110	MAXIMUM LOAD AND PRESSURE ON SIDEWALL					
kPa	480	520	550	590	620	660	690	720	760						
LBS	SINGLE	9090	9540	9880	10420	10840	11350	11670	12080	12350		S	6175	LBS at 110	PSI
	DUAL	16540	17360	18160	18960	19720	20820	21240	21980	22700		D	5675	LBS at 110	PSI
kPa	SINGLE	4120	4320	4480	4720	4920	5150	5300	5480	5600		S	2800	KG at 760	kPa
	DUAL	7480	7880	8240	8600	8960	9440	9640	9960	10300		D	2575	KG at 760	kPa

Industry load and inflation standards are in a constant state of change, and BFGoodrich continually updates its product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum air pressure limitation.